

1. VERTICAL CNC TURNING LATHE
2. HORIZONTAL CNC LATHE
3. WHY CHOOSE YONGSHUO CNC MACHINE?
4. OUR PRICE SYSTEM & PARTNERS

END:THANKS



YONGSHUO CNC MACHINING CENTERS



Email: info@superimagetech.com; Cell: 0086-131-6238-1655

PART ONE

YONGSHUO(SUPERIMAGE) VERTICAL CNC LATHE

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§VTC: VERTICAL CNC TURNING LATHE-(1):VTC-500



DIGITAL CONTROL MACHING TOOL
DIGITAL CONTROL CNC MACHINE
MULTI-FUNCTION MACHING TOOL
ECONOMIC CNC LATHE/CNC TOOL



TECHNICAL DATA	YTC-500
MAX. TURNING DIAMETER	600MM
MAX. CUTTING DIAMETER	500MM
SPINDLE MODE	A2-8
SPINDLE RPM	80-1200 RPM
SPINDLE MOTOR POWER	15KW
RATED TORQUE	191NM
XZ SERVER MOTOR	2.4KW, 10NM/2.4KW, 15NM
CHUCK DIAMETER & MODE	400/K3L
X AXIS TRAVELING DISTANCE	-250MM, +480MM
Z AXIS TRAVELING DISTANCE	700MM
TOOL POST	ROW TOOL HOLDER
ELECTRIC TOOL HOLDER	4/6 TOOLS
HYDRAULIC/DRKVEN TOOL HOLDER	8/12 TOOLS
XZ AXIS MOVING SPEED	18M/MIN
COLUMN GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:520MM; LINEAR RAIL:480MM
BEAM GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:400MM; LINEAR RAIL:380MM
CNC LATHE SIZE	1205*1200*2430MM
MACHINE WEIGHT	3000KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§VTC: VERTICAL CNC TURNING LATHE-(2):VTC-700



DIGITAL CONTROL MACHING TOOL
DIGITAL CONTROL CNC MACHINE
MULTI-FUNCTION MACHING TOOL
ECONOMIC CNC LATHE/CNC TOOL



TECHNICAL DATA	YTC-700
MAX. TURNING DIAMETER	800MM
MAX. CUTTING DIAMETER	700MM
SPINDLE MODE	A2-8/A2-11
SPINDLE RPM	80-1200 RPM
SPINDLE MOTOR POWER	18.5KW/22KW
RATED TORQUE	236NM
XZ SERVER MOTOR	2.4KW, 15NM/2.4KW, 15NM
CHUCK DIAMETER & MODE	500/K3L
X AXIS TRAVELING DISTANCE	-300MM, +550MM
Z AXIS TRAVELING DISTANCE	800MM
TOOL POST	ROW TOOL HOLDER
ELECTRIC TOOL HOLDER	4/6 TOOLS
HYDRAULIC/DRIVEN TOOL HOLDER	8/12 TOOLS
XZ AXIS MOVING SPEED	15M/MIN
COLUMN GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:620MM; LINEAR RAIL:550MM
BEAM GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:450MM; LINEAR RAIL:400MM
CNC LATHE SIZE	1500*1360*2760MM
MACHINE WEIGHT	4500KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§VTC: VERTICAL CNC TURNING LATHE-(3):VTC-900



TECHNICAL DATA	YTC-900
MAX. TURNING DIAMETER	1000MM
MAX. CUTTING DIAMETER	900MM
SPINDLE MODE	A2-11
SPINDLE RPM	80-1000 RPM
SPINDLE MOTOR POWER	18.5KW/22KW
RATED TORQUE	236NM/280NM
XZ SERVER MOTOR	2.8KW, 18NM/2.8KW, 18NM
CHUCK DIAMETER & MODE	630/K3L
X AXIS TRAVELING DISTANCE	-300MM, +620MM
Z AXIS TRAVELING DISTANCE	900MM
TOOL POST	ROW TOOL HOLDER
ELECTRIC TOOL HOLDER	4/6 TOOLS
HYDRAULIC/DRIVEN TOOL HOLDER	8/12 TOOLS
XZ AXIS MOVING SPEED	18M/MIN
COLUMN GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:700MM; LINEAR RAIL:600MM
BEAM GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:480MM; LINEAR RAIL:425MM
CNC LATHE SIZE	1550*1760*3067MM
MACHINE WEIGHT	5500KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§VTC: VERTICAL CNC TURNING LATHE-(4):VTC-1200



DIGITAL CONTROL MACHING TOOL
DIGITAL CONTROL CNC MACHINE
MULTI-FUNCTION MACHING TOOL
ECONOMIC CNC LATHE/CNC TOOL

TECHNICAL DATA	YTC-1200
MAX. TURNING DIAMETER	1250MM
MAX. CUTTING DIAMETER	1200MM
SPINDLE MODE	A2-11/A2-15
SPINDLE RPM	80-1000 RPM
SPINDLE MOTOR POWER	22KW/30KW
RATED TORQUE	280NM/382NM
XZ SERVER MOTOR	3.6KW, 23NM/3.6KW, 23NM
CHUCK DIAMETER & MODE	810/K3L
X AXIS TRAVELING DISTANCE	-270MM, +720MM
Z AXIS TRAVELING DISTANCE	1000MM
TOOL POST	ROW TOOL HOLDER
ELECTRIC TOOL HOLDER	4/6 TOOLS
HYDRAULIC/DRKVEN TOOL HOLDER	8/12 TOOLS
XZ AXIS MOVING SPEED	15M/MIN
COLUMN GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:740MM; LINEAR RAIL:650MM
BEAM GUIDE RAIL SPAN/CENTER DISTANCE	HEAVRY RAIL:500MM; LINEAR RAIL:450MM
CNC LATHE SIZE	1650*1860*3070MM
MACHINE WEIGHT	6500KG

2

PART TWO

YONGSHUO(SUPERIMAGE) HORIZONTAL CNC LATHE

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(1):CK40



TECHNICAL DATA	HTC-CK40
MAX. TURNING DIAMETER	320MM
MAX.TRAVEL DISTANCE OF TURRET SLIDE	300MM
MAX. TURNING DIAMETER OF TURRET SLIDE	100MM
MAX. PROCESSING LENGTH	180MM
THROUGH-HOLE DIAMETER OF SPINDLE	48MM
SPINDLE MOTOR POWER	3.0KW
FEEDING MOTOR POWER	1.2KW
SPINDLE ROTAING SPEED	2000RPM
X,Z AXIS LINEAR RAIL MODE	35/30
TOOL POST	ROW TOOL HOLDER
MAX. TOOL SIZE	16*16
TOOL QUANTITY	2PCS OF ROW TOOL HOLDERS
TOOL HOLDING METHOD	PNEUMATIC
CONTROL SYSTEM	GSK928TA2
CONTROL AXIS QUANTITY	X+Z,+SPINDLE
CONTROL MODE	SEMI-CLOSED LOOP
CNC LATHE SIZE	1750*1550*1650MM
MACHINE WEIGHT	1000KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(2):CK6140



TECHNICAL DATA	HTC-CK6140
MAX. TURNING DIAMETER	400MM
MAX. TURNING DIAMETER OF TURRET SLIDE	210MM
MAX. PROCESSING LENGTH	750MM
LATHE BED WIDTH	360MM
X AXIS TRAVELING DISTANCE	230MM
Z AXIS TRAVELING DISTANCE	750MM
SPINDLE ROTATING SPEED	30-500-2000 RPM(FREQUENCY)
SPINDLE END SIZE	C6
SPINDLE TAPER	MT6
THROUGH-HOLE DIAMETER OF SPINDLE	52MM
SPINDLE MOTOR POWER	5.5KW
X,Z SERVER MOTOR	6.0NM
TOOL QUANTITY	4/6
TOOL HOLDER SIZE	25*25
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	3000/6000 MM/MIN
CNC LATHE SIZE	2060*1200*1500MM
MACHINE WEIGHT	1700KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(3):CK6136



DIGITAL CONTROL MACHING TOOL
DIGITAL CONTROL CNC MACHINE
MULTI-FUNCTION MACHING TOOL
ECONOMIC CNC LATHE/CNC TOOL

TECHNICAL DATA	HTC-CK6136
MAX. TURNING DIAMETER	360MM
MAX. TURNING DIAMETER OF TURRET SLIDE	180MM
MAX. PROCESSING LENGTH	850MM
LATHE BED WIDTH	360MM
X AXIS TRAVELING DISTANCE	210MM
Z AXIS TRAVELING DISTANCE	850MM
SPINDLE ROTATING SPEED	250-700/500-1600RPM(FREQUENCY)
SPINDLE END SIZE	C6
SPINDLE TAPER	MT6
THROUGH-HOLE DIAMETER OF SPINDLE	52MM
SPINDLE MOTOR POWER	5.5KW
X,Z SERVER MOTOR	4.0/6.0NM
TOOL QUANTITY	6/8
TOOL HOLDER SIZE	20*20
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	3000/6000 MM/MIN
CNC LATHE SIZE	2350*1500*1700MM
MACHINE WEIGHT	1800KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(4):CK6150



TECHNICAL DATA	HTC-CK6150
MAX. TURNING DIAMETER	500MM
MAX. TURNING DIAMETER OF TURRET SLIDE	280MM
MAX. PROCESSING LENGTH	1000MM
LATHE BED WIDTH	390MM
X AXIS TRAVELING DISTANCE	295MM
Z AXIS TRAVELING DISTANCE	1000MM
SPINDLE ROTATING SPEED	20-130/100-600/200-1600RPM(FREQUENCY)
SPINDLE END SIZE	C8
SPINDLE TAPER	90/1:20
THROUGH-HOLE DIAMETER OF SPINDLE	82MM
SPINDLE MOTOR POWER	7.5KW
X,Z SERVER MOTOR	8.0NM
TOOL QUANTITY	4/6
TOOL HOLDER SIZE	25*25
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	6000/10000 MM/MIN
CNC LATHE SIZE	3000*1700*2010MM
MACHINE WEIGHT	2730KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(5):CK6160



DIGITAL CONTROL MACHING TOOL
DIGITAL CONTROL CNC MACHINE
MULTI-FUNCTION MACHING TOOL
ECONOMIC CNC LATHE/CNC TOOL

TECHNICAL DATA	HTC-CK6160
MAX. TURNING DIAMETER	630MM
MAX. TURNING DIAMETER OF TURRET SLIDE	280MM
MAX. PROCESSING LENGTH	1000MM
LATHE BED WIDTH	390MM
X AXIS TRAVELING DISTANCE	320MM
Z AXIS TRAVELING DISTANCE	1000MM
SPINDLE ROTATING SPEED	20-2000RPM(FREQUENCY)
SPINDLE END SIZE	C8
SPINDLE TAPER	90/1:20
THROUGH-HOLE DIAMETER OF SPINDLE	82MM
SPINDLE MOTOR POWER	11.0KW
X,Z SERVER MOTOR	10.0NM
TOOL QUANTITY	4/6
TOOL HOLDER SIZE	25*25
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	5000/8000 MM/MIN
CNC LATHE SIZE	3000*1800*2010MM
MACHINE WEIGHT	2860KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(6):CK6180



DIGITAL CONTROL MACHING TOOL
DIGITAL CONTROL CNC MACHINE
MULTI-FUNCTION MACHING TOOL
ECONOMIC CNC LATHE/CNC TOOL

TECHNICAL DATA	HTC-CK6180-1000
MAX. TURNING DIAMETER	800MM
MAX. TURNING DIAMETER OF TURRET SLIDE	400MM
MAX. PROCESSING LENGTH	1000
LATHE BED WIDTH	400MM
X AXIS TRAVELING DISTANCE	390MM
Z AXIS TRAVELING DISTANCE	1000MM
SPINDLE ROTATING SPEED	25-850RPM(FREQUENCY & STEPLESS)
SPINDLE END SIZE	C8
SPINDLE TAPER	METRIC STANDARD: 120 1:20
THROUGH-HOLE DIAMETER OF SPINDLE	100MM
SPINDLE MOTOR POWER	11.0KW
X,Z SERVER MOTOR	12.0NM
TOOL QUANTITY	4
TOOL HOLDER SIZE	25*25
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	4000/5000 MM/MIN
CNC LATHE SIZE	3200*1820*1780MM
MACHINE WEIGHT	3900KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(7):CK6180



TECHNICAL DATA	HTC-CK6180-1500
MAX. TURNING DIAMETER	800MM
MAX. TURNING DIAMETER OF TURRET SLIDE	400MM
MAX. PROCESSING LENGTH	1500
LATHE BED WIDTH	400MM
X AXIS TRAVELING DISTANCE	390MM
Z AXIS TRAVELING DISTANCE	1500MM
SPINDLE ROTATING SPEED	25-850RPM(FREQUENCY & STEPLESS)
SPINDLE END SIZE	C8
SPINDLE TAPER	METRIC STANDARD(120)- 1:20
THROUGH-HOLE DIAMETER OF SPINDLE	100MM
SPINDLE MOTOR POWER	11.0KW
X,Z SERVER MOTOR	12.0NM
TOOL QUANTITY	4
TOOL HOLDER SIZE	25*25
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	4000/5000 MM/MIN
CNC LATHE SIZE	3700*1820*1780MM
MACHINE WEIGHT	4600KG

YONGSHUO CNC MACHINING CENTER

Part One –Specification & Model of VTC

§HTC: HORIZONTAL CNC TURNING LATHE-(8):CK6180



TECHNICAL DATA	HTC-CK6180-3000
MAX. TURNING DIAMETER	800MM
MAX. TURNING DIAMETER OF TURRET SLIDE	400MM
MAX. PROCESSING LENGTH	3000
LATHE BED WIDTH	400MM
X AXIS TRAVELING DISTANCE	390MM
Z AXIS TRAVELING DISTANCE	3000MM
SPINDLE ROTATING SPEED	25-850RPM(FREQUENCY & STEPLESS)
SPINDLE END SIZE	C8
SPINDLE TAPER	METRIC STANDARD(120)- 1:20
THROUGH-HOLE DIAMETER OF SPINDLE	100MM
SPINDLE MOTOR POWER	11.0KW
X,Z SERVER MOTOR	12.0NM
TOOL QUANTITY	4
TOOL HOLDER SIZE	25*25
TOOL CHANGING TIME	2 SECONDS
X,Z FEEDING SPEED	4000/5000 MM/MIN
CNC LATHE SIZE	5200*1820*1780MM
MACHINE WEIGHT	6400KG

PRICE SYSTEM & PARTNERS OF YONGSHUO CNC MACHINING CENTER

Part Eight – The price system & partners of Yongshuo CNC Machine



(Order Quantity: 50Sets)



(Order Quantity: 30Sets)



(Order Quantity: 90Sets)



(Order Quantity: 70Sets)



(Order Quantity: 60Sets)



(Order Quantity: 30Sets)

THANKS



Email: info@superimagetech.com; Cell: 0086-131-6238-1655